

MOCROPERFORADO VINYL 180 MIC

SPECIFICATION

- Soft, clear white monomeric 180mic self adhesive PVC film for smooth printing.
- Dynamic prints, perfect visibility due to 60:40 balance between vinyl and holes.
- Suitable for (eco) solvent, UV and LATEX.
- Special double liner to suit UV and LATEX printing.
- Indoor/Outdoor use.
- Easy to remove up till 6 months after application

FOLLOW US:

SPECIFICATION

DESCRIPTION

PVC

Typ

Calendered monomeric soft PVC film

Thickness 180 + 10 um

Color Code White

Back Black

Shrinkage < 0.6%

Surface Tension > 30dn/cm

Opacity > 99%

Holes No. Average 130/sq in

Hole diameter 1.6 mm

Distance between holes 2.4 mm

Holes space 41%

ADHESIVE

Type

Clear solvent based removable pressure sensitive glue

Weight (g/m²) 30 + 2

Adhesion temperature 15°C-40°C

180° peeling force < 5N/25mm 20min

Initial Adhesion-ball tack > 5# Steel ball

Holding power > 800min

Removable One year cleanly removable glue on clean glass surface at temperature of

	Durability	23-25°C and RH of 50-60%
LINER	Type	Laminated kraft paper (Additional liner)
Color		White
Weight		240g + 5g/m ²

STORAGE PERIOD 12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%.

APPLICATION One way vision: Outdoor digital and silk screen printing media for vehicle graphics, airport graphics, subway window, platform graphics, glass walls of building and signage display applications.

COMPATIBILITY

MACHINES & INKS

Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original inks from the printer manufactures.

The best printing temperature is 35-40°C.