

ImagePerfect™ 2411 Wallpaper Canvas is a washable paper for wall decorations. This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2411

ImagePerfect™ 2411 Wallpaper Canvas is a printable wallpaper with a canvas look structure. Due to its non-woven backing, this wallpaper is very easy to apply with wallpaper paste (for non-woven liner) and has first-class removability. The printed material can be cleaned with warm water, soap and a soft sponge, and the printed graphics are also very scrub resistant. Test results can be categorized as the highest standard in the wall paper industry. IP 2411 can be used to personalize home interiors, show rooms, trade shows, events, hotels, restaurants and many more environments.

Wallpaper paste recommendation: Henkel or Quelyd. Look for 'non-woven' quality in general which can be found in most Do-It-Yourself shops

Specifications	
DESCRIPTION	Wallpaper
COLOUR	White matt
THICKNESS	330μ
WEIGHT	240g/m <sup>2</sup>
ADHESIVE	N/A
RELEASE PAPER	N/A
TEMPERATURE RANGE	N/A
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	Euro-Class: C-s2, d0 (EN13501-1)
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© August 2014 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased. Also for horizontal applications, exterior performance will be decreased.

Print-Media have to be properly dried before further processing, like laminating, varnishing or application. The residual solvents can otherwise change the products' specific features.

ImagePerfect™ 2412 Wallpaper Sandblast is a highly washable paper for wall decorations. This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2412

ImagePerfect™ 2412 Wallpaper Sandblast is a printable wallpaper with a sandblast look structure. Due to its non-woven backing, this wallpaper is very easy to apply with wallpaper paste (for non-woven liner) and has first-class removability. The printed material can be cleaned with warm water, soap and a soft sponge, and the printed graphics are also very scrub resistant. Test results can be categorized as the highest standard in the wallpaper industry. IP 2412 can be used to personalize home interiors, show rooms, trade shows, events, restaurants, hotels and many more environments.

Wallpaper paste recommendation: Henkel or Quelyd. Look for 'non-woven' quality in general which can be found in most Do It Yourself shops

Specifications	
DESCRIPTION	Wallpaper
COLOUR	White matt
THICKNESS	330μ
WEIGHT	240g/m <sup>2</sup>
ADHESIVE	N/A
RELEASE PAPER	N/A
TEMPERATURE RANGE	N/A
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	Euro-Class: C-s2, d0 (EN13501-1)
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© March 2013 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased. Also for horizontal applications, exterior performance will be decreased.

Print-Media have to be properly dried before further processing, like laminating, varnishing or application. The residual solvents can otherwise change the products' specific features.

**Distributed by Spandex. [www.spandex.com](http://www.spandex.com)**

**Spandex Group**, Excelsiorlaan 55, B-1930 Zaventem, Belgium  
Tel. +32 (0)2 725 73 70 | Fax +32 (0)2 720 76 40 | [www.spandex.com](http://www.spandex.com)



IP 2415 is a high quality, highly washable paper for wall decoration. It has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks, as well as UV-cured inks.

## IP 2415

ImagePerfect™ 2415 is a printable wallpaper with a look and structure that closely resemble a 'standard' wallpaper. Due to its non-woven backing, this wallpaper is very easy to apply with wallpaper glue (for non-woven liner) and has first-class removability. The printed material can be cleaned with warm water, soap and a soft sponge, with the printed graphics being very scrub resistant. The product's special topcoating promotes high levels of printability, such that test results can be categorized as the highest standard in the wallpaper industry. IP 2415 can be used to personalise home interiors, offices, show rooms, trade shows, and in many event and lifestyle application environments such as restaurants, bars, hotels.

Specifications	
DESCRIPTION	Wallpaper
COLOUR	White matt
THICKNESS	330μ
WEIGHT	210g / m <sup>2</sup>
ADHESIVE	N/A
RELEASE PAPER	N/A
TEMPERATURE RANGE	N/A
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	Euro-Class: C-s2, d0 (EN13501-1)
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© March 2013 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased. Also for horizontal applications, exterior performance will be decreased.

Print-Media have to be properly dried before further processing, like laminating, varnishing or application. The residual solvents can otherwise change the products' specific features.

**Distributed by Spandex. [www.spandex.com](http://www.spandex.com)**

**Spandex Group**, Excelsiorlaan 55, B-1930 Zaventem, Belgium  
Tel. +32 (0)2 725 73 70 | Fax +32 (0)2 720 76 40 | [www.spandex.com](http://www.spandex.com)

